



Industrie Service

CERTIFICATE

0036 CPD 9195 018

Revision 01

In compliance with the Directive 89/106/EEC of the Council of European Communities of 21st December 1988 on the approximation of laws, regulations and administrative provisions of the Member States relating to the construction products (Construction Products Directive – CPD) amended by the Directive 93/68/EEC of the Council of European Communities of 22nd July 1993, it has been stated that the construction product

System Chimney PRIMA PLUS models

model 1	EN 1856-1	T200 P1 W V2 L50060 OXXX
model 2	EN 1856-1	T450 N1 W V2 L50060 GXXX
model 3	EN 1856-1	T450 N1 D V3 L50060 GXXX

1) for details of designation see second page of certificate

produced by

**Schiedel Chimney Systems Ltd.
Crowther Estate
Washington, Tyne & Wear, NE38 0AQ (GB)**

in the factory

**Schiedel Chimney Systems Ltd.
Washington, Tyne & Wear, NE38 0AQ (GB)**

is submitted to

- the **initial type testing**, performed by TÜV SÜD Industrie Service GmbH, test reports A 1399-03/06, A 1399-12/11 and A 1793-00/09 as well as
- a **factory production control**

The Notified Body TÜV SÜD Industrie Service GmbH has performed the initial inspection of the factory and the factory production control and performs the continuous surveillance, assessment and approval of the factory production control.


This certificate attests that all provisions concerning the attestation of factory production control described in Annex ZA of the standard

EN 1856-1: 2009-06

were applied.

This certificate was first issued on 2007-06-06 and - with respect to the conditions of the certification contract - remains valid as long as the conditions laid down in the harmonised technical specification in reference or the manufacturing conditions in the factory or the FPC itself are not modified significantly.

Munich, 2011-02-24


.....
J. Steiglechner



Industrie Service

<p>PRIMA PLUS single wall installation DN 80 – DN 300 DN 350 – DN 400</p>	<p>T200 P1 W V2 L50060 O200 T200 P1 W V2 L50060 O300</p>
<p>install. in an insulated enclosure specified by manufacturer DN 80 – DN 300 DN 350 – DN 400</p>	<p>T450 N1 W V2 L50060 G50 T450 N1 W V2 L50060 G75</p>
<p>with insulation for installation in an outer liner DN 80 – DN 300 DN 350 – DN 400</p>	<p>T450 N1 D V3 L50060 G75 T450 N1 D V3 L50060 G112,5</p>